

LAND

Entel

ATEX 

II 2 G Ex ib IIA T4
II 2 G Ex ib IIC T4

 IECEX

Ex ib IIC T4

Submersible
Intelligent
Tough



HT Series 2.0

HT series features



Pictured: Radio with optional stubby antenna and CSAHT rapid charger

HT Series 2.0 – a model for every application. From entry level to sophisticated MPT1327 trunked variants, the HT Series 2.0 is built without compromise to deliver loud and crisp audio using the latest compander noise reduction technology.

Submersible – conforming to European IP68, the HT Series 2.0 offers the highest submersibility rating of any manufacturer. This unique series protects against corrosion, withstanding total immersion in water to a depth of 5 metres for 1 hour to protect against the likely hazards encountered in any field of operation.

Commercial Grade Construction – exceeding MIL STD 810C/D/E/F rating for tough enduring performance the HT Series 2.0 is designed to withstand shock, vibration, dust and moisture, ensuring many years of trouble free use in the most hostile environments.

Simple Or Sophisticated – you choose. Need simple speech communications? Then our entry level PMR radios will meet all your needs. Entel's mid level radios give you all the facilities you might expect from our competitors' products, while our top of the range radio is arguably the most versatile radio you can buy.

Intelligent Lithium-Ion Battery With Built In Charge Cycle Monitoring – this very latest technology gives you four essential advantages:

- 1) For your convenience the HT Series 2.0 will count charge cycles of your battery pack, warning you when it is nearing the end of its life. Models equipped with an LCD will also display the battery charge count.
- 2) Extended duty cycle.
- 3) Not prone to the dreaded memory effect that Nicad and Ni-MH battery packs suffer from, therefore no need to fully discharge your battery pack before charging.
- 4) Stores a charge up to three times longer than a Nicad battery.

ATEX Approved IIC – the HT900 range of ATEX certified portables meet IIC T4 – the most stringent ATEX rating as per EU directive 94/9/EC. For full details refer to the ATEX DATA SHEET available here: www.entel.co.uk/atex

ATEX Approved IIA – the HT800 range of ATEX certified portables meet IIA T4 for those requiring lower cost ATEX equipment for use in a less hazardous environment. This classification offers the maximum RF power output (up to 5 watts).

Model Selection:



Not Intrinsicly Safe	Land VHF (30 - 50MHz)	HT702	HT702S	HT703	HT705	HT706
	Land VHF (66 - 88MHz)	HT712	HT712S	HT713	HT715	HT716
	Land VHF (136 - 174MHz)	HT722	HT722S	HT723	HT725	HT726
	Land UHF (400 - 470MHz) [450 - 520MHz]	HT782 [HT782U]	HT782S [HT7825U]	HT783 [HT783U]	HT785 [HT785U]	HT786 [HT786U]
	MPT1327	See MPT1327 Trunked Brochure				
	Marine	See Marine Brochure				
	PMR446	See PMR446 Brochure				
ATEX IIA Intrinsicly Safe	Land VHF (30 - 50MHz)	HT802	HT802S	HT803	HT805	HT806
	Land VHF (66 - 88MHz)	HT812	HT812S	HT813	HT815	HT816
	Land VHF (136 - 174MHz)	HT822	HT822S	HT823	HT825	HT826
	Land UHF (400 - 470MHz) [450 - 520MHz]	HT882 [HT882U]	HT882S [HT8825U]	HT883 [HT883U]	HT885 [HT885U]	HT886 [HT886U]
	MPT1327	See MPT1327 Trunked Brochure				
	Marine	See Marine Brochure				
	PMR446	See PMR446 Brochure				
ATEX IIC Intrinsicly Safe	Land VHF (30 - 50MHz)	HT902	HT902S	HT903	HT905	HT906
	Land VHF (66 - 88MHz)	HT912	HT912S	HT913	HT915	HT916
	Land VHF (136 - 174MHz)	HT922	HT922S	HT923	HT925	HT926
	Land UHF (400 - 470MHz) [450 - 520MHz]	HT982 [HT982U]	HT982S [HT9825U]	HT983 [HT983U]	HT985 [HT985U]	HT986 [HT986U]
	MPT1327	See MPT1327 Trunked Brochure				
	Marine	See Marine Brochure				
	PMR446	See PMR446 Brochure				



Entry



Entry Selcall



Entry LCD



Advanced Signalling



Advanced Signalling Keypad

General Features

Environmental protection to IP68 (submersible - 5m for 1 hour)	✓	✓	✓	✓	✓
MIL STD 810C/D/E/F	✓	✓	✓	✓	✓
1800mAh Li-Ion battery	✓	✓	✓	✓	✓
Flash upgradeable to add future features	✓	✓	✓	✓	✓
Robust accessory socket	✓	✓	✓	✓	✓
Programmable accessory connector	✗	✓	✗	✓	✓
Number of channels	16	16	255	255	255
LCD display	✗	✗	✓	✓	✓
Scrolling graphics	✗	✗	✗	✓	✓
Channel naming	✗	✗	✓	✓	✓
Multi-function encoder control	✗	✗	✓	✓	✓
Scan/priority scan	✓	✓	✓	✓	✓
Voice annunciation (option)	✓	✓	✓	✓	✓
Bluetooth wireless comms (option)	✓	✓	✓	✓	✓
Clone data from one radio to another	✓	✗	✓	✗	✗
Voting	✗	✓	✗	✓	✓
Display custom logo at switch on	✗	✗	✓	✓	✓

For - Convenience

VOX hands free	✓	✓	✓	✓	✓
Programmable channel monitor button	✓	✓	✓	✓	✓
2/5 tone selective calling	✗	✓	✗	✓	✓
Open or Closed channel modes	✗	✓	✗	✓	✓
Call all radios at once	✓	✓	✓	✓	✓
Call a group or individual radios	✗	✓	✗	✓	✓
16 pre-programmed contacts	✗	✓	✗	✗	✗
400 user contact list (just like a mobile phone)	✗	✗	✗	✓	✓
Multiple ringtones	✗	✓	✗	✓	✓
Battery charge count (requires LCD to display)	✓	✓	✓	✓	✓
Battery level indicator	✗	✗	✓	✓	✓
Low battery warning	✓	✓	✓	✓	✓
Receive signal strength indicator	✗	✗	✓	✓	✓
Talkaround	✓	✓	✓	✓	✓
Intuitive menus (like a mobile phone)	✗	✗	✗	✓	✓
Info button (user guide built in to radio)	✗	✗	✗	✓	✓
Speed dial	✗	✗	✗	✓	✓
Who's calling (caller ID)	✗	✗	✗	✓	✓
Missed, received & dialled numbers lists	✗	✗	✗	✓	✓
4 "channel shortcut" buttons	✓	✓	✓	✓	✓
DTMF dial mode	none	stored	none	stored	stored/keypad

For - Security

Stun a lost or stolen radio (& revive if found)	✗	✓	✗	✓	✓
Programmable scrambler	option	✓	option	✓	✓
Power on password option	✗	✗	✗	✓	✓

For - Safety

Local Personal Attack Alarm	✓	✓	✓	✓	✓
Panic button with remote alert	✗	✓	✗	✓	✓
Emergency microphone live	✗	✓	✗	✓	✓
Lone Worker alarm mode	✗	✓	✗	✓	✓
Man Down basic (option)	✗	✓	✗	✓	✓
Shunting mode (for rail companies)	✗	✓	✗	✓	✓
Whisper mode	✗	✓	✗	✓	✓
Silent alarm call mode	✗	✓	✗	✓	✓
Continue alarm even if switched off	✗	✓	✗	✓	✓
Manual location information with emergency	✗	✗	✗	✓	✓
Bluetooth fully automatic indoor location (option)	none	send	none	send/display	send/display

For - Text Messaging

Status messages	none	send	none	send/display	send/display
-----------------	------	------	------	--------------	--------------

'the professional's choice'



■ CSAHT*



■ CSBHT*



■ CMP750
▲ CMP950



■ EA19/750
▲ EA19/950



■ EA15/750
▲ EA15/950



■ EA12/750
▲ EA12/950



■ CXR5/750
▲ CXR5/950



■ CXR16/750
▲ CXR16/950



■ CHP750D
▲ CHP950D



■ CHP750HS
▲ CHP950HS

*Used to charge ATEX models in a non hazardous-environment

■ Not intrinsically Safe

▲ ATEX 

technical specifications

General Features

RF power output	VHF - 5 Watts (high) / 1 Watt (low) UHF - 4 Watts (high) / 1 Watt (low)
RF power output ATEX	IIA 4 Watts (UHF) / 5 Watts (VHF) IIC 1 Watt
Frequency range VHF Low	30 to 50MHz
Frequency range VHF Mid	66 to 88MHz
Frequency range VHF High	136 to 174MHz
Frequency range UHF	400 to 470MHz
Frequency range UHF u/band	450 to 520MHz
Channels	See general features
Environmental protection	IP68 submersible 5m for 1 hour
Military Standard	MIL STD 810C/D/E/F
Dimensions*	130mm(h) x 59.5mm(w) x 37mm(d)
Weight	277g (with battery and antenna)
Audio output	660mW - distortion: < 3% @ 500mW

*Dimensions are based on radio with attached battery, excluding knobs, antenna and protrusions.

Supplied Accessories

7.4v, 1800mAh Li-Ion battery

CSAHT rapid charger is included with HTxx2, HTxx2S and HTxx3

Spring loaded belt clip

High efficiency antenna

User guide CD

For a full and detailed specification see our web site www.entel.co.uk

Your local professional dealer

